



MVOICE 1010 Series USB/Bluetooth Conference Speakerphone

For personal and small group conferencing

MVOICE 1010 series conference speakerphones are specially designed for small business conference room, home based worker etc. who need professional audio endpoint for web-conferencing and video conferencing, to replace the PCs and mobile phone's speaker and microphone with outstanding audio quality.

Easy Set Up

Easy connect to your PC or laptop via USB, works great with PC based communication softphone i.e Skype,Zoom etc.

- Wireless conference with Bluetooth

Support connection to mobile phone via Bluetooth, turn your mobile phone as a conference gateway anytime anywhere. (MVOICE 1010-B only)

10' Microphone Pick Up

Each one speakerphone can pick up the sound with a 10' x 10' range with crystal clear audio.

Clean and Crisp Audio Quality

Let the far end hear clearly with our advanced audio algorithm, intelligent noise cancellation and powerful audio output.

Wide Software Compatibility

Works with virtually every online video conferencing software with no need for additional drivers or proprietary connections.

Battery Built-in

The built -in Li-ion battery supports over 4 hours continuous talk time



PHOTO Image: Constraint of the system of	SPECIFICATIONS	MVOICE 1010	MVOICE 1010-B
Recommended room coverage10-15m'10-15m'Conference size8-10 persons8-10 personsMicrophone	рното	0000	
Conference size8-10 persons8-10 personsMicrophone16ft (5m)16ft (5m)Microphone response frequency30Hz-16KHz30Hz-16KHzBuilt-in Mic33SpeakerMax output(dB)89dB89dBSpeaker response frequency30Hz-16KHz30Hz-16KHzAudioVVVFull DuplexVVDynamic Noise Reduction (DNR)VVAutomatic Gain Control (AGC)VVUSB cableVVUSB cableVVIbluetooth connectivityN/ABT Version:3.0Buetooth connectivityN/ABT Version:3.0Buetooth connectivityN/AUrersion:3.0Bluetooth connectivityN/AVN/AUnit DimensionsФ140 x 32mmPackageUSB cable0.5kgOs requirements0.5kg0.5kgAccessoriesProtective Travel Case USB cable, English User's ManualEnvironmentsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOS requirements30°C—55°C-30°C—55°CRechargeable batteryN/AVer 4-hours talk time	Recommended Situations		
Conference size8-10 persons8-10 personsMicrophone		10-15 m²	10-15 m ²
Microphone16ft (5m)16ft (5m)Sound pick up range16ft (5m)30Hz-16KHzBuilt-in Mic33Speaker33Max output(dB)89dB89dBSpeaker response frequency30Hz-16KHz30Hz-16KHzAudioFull DuplexVVDynamic Noise Reduction (DNR)VVAutomatic Gain Control (AGC)VVUSB cableVVBluetooth connectivityN/ABT Version:3.0BT version:3.0BT Version:3.0BT Version:3.0Bt version:3.0BT Version:3.0BT version:3.0Buetooth connectivityN/AIf or external speakerPackageUnit DimensionsФ140 x 32mmФ140 x 32mmPackage Dimensions245x170x50mm245x170x50mmPackage Weight0.5kg0.5kgAccessoriesProtective Travel Case USB cable,English User's ManualEnvironmentsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOS requirementsS°C-40°C5°C-40°COS requirementsS°C-40°C5°C-40°COS requirementsS°C-55°C-30°C-55°CAccessoriesWindows XP/ Vista/ 7/8/10 Mac OS, AndroidVindows talk time		8-10 persons	8-10 persons
Sound pick up range16ft (5m)16ft (5m)Microphone response frequency30Hz-16KHz30Hz-16KHzBuilt-in Mic33SpeakerMax output(dB)89dB89dBSpeaker response frequency30Hz-16KHz30Hz-16KHzAudioFull DuplexVVAutomatic Gain Control (AGC)VVOnnectivityUSB cableVVBluetooth connectivityN/ABT Version:3.0Bry Forflie:HSP / HFP / A2DPBT version:3.0Bry Forflie:HSP / HFP / A2DPWireless output:Class 2Max.communication distance:30meters1 for external speaker3.5mm audio port1 for external speaker1 for external speakerPackageUSBUnit DimensionsФ140 x 32mmФ140 x 32mmPackage Weight0.5kg0.5kgAccessoriesProtective Travel Case USB cable,English User's ManualEnvironmentsUSB cable,English User's ManualOS requirementsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOperating temperature5°C—40°C5°C - 40°C Os °C - 55°C√VN/AVVRechargeable batteryN/AV	Microphone		
Microphone response frequency30Hz-16KHz30Hz-16KHzBuilt-in Mic33SpeakerMax output(dB)89dB89dBSpeaker response frequency30Hz-16KHz30Hz-16KHzAudioFull DuplexVVPuln DuplexVVAutomatic Gain Control (AGC)VVUSB cableVVBluetooth connectivityN/ABT Version:3.0BT Version:3.0BT Version:3.0BT Version:3.0Btuetooth connectivityN/ABT Version:3.0Buetooth connectivityN/AMax.communication distance:30meters3.5mm audio port1 for external speaker1 for external speakerPackageUnit DimensionsФ140 x 32mmФ140 x 32mmPackage Weight0.5kg0.5kgAccessoriesUSB cable,English User's ManualEnvironmentsS°C-40°C5°C-40°COS requirementsS°C-40°C5°C-40°COS requirements-30°C-55°C-30°C-55°COperating temperature5°C-40°C5°C-40°CStorage temperature-30°C-55°C-30°C-55°CRechargeable batteryN/AVer 4-hours talk time	· · · · · · · · · · · · · · · · · · ·	16ft (5m)	16ft (5m)
SpeakerMax output(dB)89dB89dBMax output(dB)89dB89dBSpeaker response frequency30Hz-16KHz30Hz-16KHzAudioVVFull DuplexVVDynamic Noise Reduction (DNR)VVAutomatic Gain Control (AGC)VVConnectivityVVUSB cableVVBluetooth connectivityN/ABT Version:3.0BT profile:HSP / HFP / A2DPWireless output:Class 2Max.communication distance:30metersMax.communication distance:30meters3.5mm audio port1 for external speaker1 for external speakerPackageUnit DimensionsФ140 x 32mm 0.5kgФ140 x 32mmPackage Weight0.5kg0.5kg0.5kgAccessoriesProtective Travel Case USB cable,English User's ManualProtective Travel Case USB cable,English User's ManualEnvironmentsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOperating temperature5°C—40°C5°C—40°C 0°CStorage temperature-30°C—55°C 0.0°C-30°C—55°CRechargeable batteryN/AVOver 4-hours talk time		30Hz-16KHz	30Hz-16KHz
Max output(dB)89dB89dBSpeaker response frequency30Hz-16KHz30Hz-16KHzAudioV30Hz-16KHzFull DuplexVVDynamic Noise Reduction (DNR)VVAutomatic Gain Control (AGC)VVConnectivityVVUSB cableVVBluetooth connectivityN/ABT Version:3.0 BT profile:HSP / HEP / A2DP Wireless output:Class 2 Max.communication distance:30meters3.5mm audio port1 for external speaker1 for external speakerPackageUnit DimensionsФ140 x 32mmPackage Dimensions245x170x50mm245x170x50mmPackage Weight0.5kg0.5kgAccessoriesProtective Travel Case USB cable,English User's ManualEnvironmentsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOperating temperature5°C—40°C -30°C—55°CVRechargeable batteryN/AV	Built-in Mic	3	3
Speaker response frequency30Hz-16KHz30Hz-16KHzAudioVVFull DuplexVVDynamic Noise Reduction (DNR)VVAutomatic Gain Control (AGC)VVConnectivityVVUSB cableVVBluetooth connectivityN/ABT Version:3.0BT profile:HSP / HFP / A2DPWireless output:Class 2Max.communication distance:30meters1 for external speaker3.5mm audio port1 for external speaker1 for external speakerPackageVVUnit DimensionsФ140 x 32mmФ140 x 32mmPackage Weight0.5kg0.5kgAccessoriesProtective Travel Case USB cable,English User's ManualProtective Travel Case USB cable,English User's ManualEnvironmentsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOperating temperature5°C — 40°C5°C — 40°CStorage temperature-30°C — 55°C-30°C — 55°CRechargeable batteryN/AV	Speaker		
Audio √ √ Full Duplex √ √ Dynamic Noise Reduction (DNR) √ √ Automatic Gain Control (AGC) √ √ Connectivity √ √ USB cable √ √ Bluetooth connectivity N/A BT Version:3.0 BT profile:HSP / HFP / A2DP Wireless output:Class 2 Max.communication distance:30meters 3.5mm audio port 1 for external speaker 1 for external speaker Package Unit Dimensions Ф140 x 32mm Ф140 x 32mm Package Dimensions 245x170x50mm 245x170x50mm Package Weight 0.5kg 0.5kg Accessories Protective Travel Case USB cable,English User's Manual Protective Travel Case USB cable,English User's Manual Environments Windows XP/ Vista/ 7/8/10 Mac OS, Android Windows XP/ Vista/ 7/8/10 Mac OS, Android Windows XP/ Vista/ 7/8/10 Mac OS, Android Operating temperature 5°C — 40°C 5°C — 40°C 5°C = 40°C Storage temperature -30°C — 55°C -30°C — 55°C -30°C — 55°C Rechargeable battery N/A V Over 4-hours talk time <td>Max output(dB)</td> <td>89dB</td> <td>89dB</td>	Max output(dB)	89dB	89dB
Full DuplexImage: space of the system of the sy	Speaker response frequency	30Hz-16KHz	30Hz-16KHz
Dynamic Noise Reduction (DNR)VVAutomatic Gain Control (AGC)VVConnectivityVVUSB cableVVBluetooth connectivityN/ABT Version:3.0 BT profile:HSP / HFP / A2DP Wireless output:Class 2 Max.communication distance:30meters3.5mm audio port1 for external speaker1 for external speakerPackageUnit DimensionsФ140 x 32mm Package DimensionsФ140 x 32mm 0.5kgPackage Weight0.5kg0.5kgAccessoriesProtective Travel Case USB cable,English User's ManualEnvironmentsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOS requirementsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOperating temperature5°C—40°C5°C—40°C\$°C—40°CStorage temperature-30°C—55°C-30°C—55°C·V Over 4-hours talk time	Audio		
Automatic Gain Control (AGC)√√ConnectivityUSB cable√√USB cable√√Bluetooth connectivityN/ABT Version:3.0 BT profile:HSP / HFP / A2DP Wireless output:Class 2 Max.communication distance:30meters3.5mm audio port1 for external speaker1 for external speakerPackageUnit DimensionsФ140 x 32mmФ140 x 32mmPackage Dimensions245x170x50mm245x170x50mmPackage Weight0.5kg0.5kgAccessoriesProtective Travel Case USB cable,English User's ManualProtective Travel Case USB cable,English User's ManualEnvironmentsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOperating temperature5°C40°C5°C40°C5°C40°CStorage temperature-30°C55°C-30°C55°C-30°C55°CRechargeable batteryN/A√ Over 4-hours talk time	Full Duplex	\checkmark	√
Connectivity√USB cable√Bluetooth connectivityN/ABluetooth connectivity<	Dynamic Noise Reduction (DNR)	\checkmark	√
USB cable√√Bluetooth connectivityN/ABT Version:3.0 BT profile:HSP / HFP / A2DP Wireless output:Class 2 Max.communication distance:30meters3.5mm audio port1 for external speaker1 for external speakerPackageUnit DimensionsФ140 x 32mmФ140 x 32mmPackage Dimensions245x170x50mm245x170x50mmPackage Weight0.5kg0.5kgAccessoriesProtective Travel Case USB cable,English User's ManualProtective Travel Case USB cable,English User's ManualEnvironmentsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOs requirements5°C—40°C5°C—40°C5°C—40°CStorage temperature-30°C—55°C-30°C—55°C-30°C—55°CRechargeable batteryN/A√ Over 4-hours talk time	Automatic Gain Control (AGC)	\checkmark	√
Bluetooth connectivityN/ABT Version:3.0 BT profile:HSP / HFP / A2DP Wireless output:Class 2 Max.communication distance:30meters3.5mm audio port1 for external speaker1 for external speakerPackageUnit DimensionsФ140 x 32mmФ140 x 32mmPackage Dimensions245x170x50mm245x170x50mmPackage Weight0.5kg0.5kgAccessoriesProtective Travel Case USB cable,English User's ManualProtective Travel Case USB cable,English User's ManualEnvironmentsOS requirementsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOperating temperature5°C—40°C5°C—40°CStorage temperature-30°C—55°C-30°C—55°CRechargeable batteryN/A	Connectivity		
Bluetooth connectivityN/ABT profile:HSP / HFP / A2DP Wireless output:Class 2 Max.communication distance:30meters3.5mm audio port1 for external speaker1 for external speakerPackageUnit DimensionsФ140 x 32mmФ140 x 32mmPackage Dimensions245x170x50mm245x170x50mmPackage Weight0.5kg0.5kgAccessoriesProtective Travel Case USB cable,English User's ManualProtective Travel Case USB cable,English User's ManualEnvironmentsOS requirementsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOperating temperature5°C—40°C5°C—40°CStorage temperature-30°C—55°C-30°C—55°CRechargeable batteryN/A	USB cable	\checkmark	√
S.Shim addio portIndirectemal speakerPackageФ140 x 32mmUnit DimensionsФ140 x 32mmPackage Dimensions245x170x50mmPackage Weight0.5kgAccessoriesProtective Travel Case USB cable, English User's ManualEnvironmentsVista/ 7/8/10 Mac OS, AndroidOS requirementsS°C—40°COperating temperature5°C—40°CStorage temperature-30°C—55°CRechargeable batteryN/A	Bluetooth connectivity	N/A	BT profile:HSP / HFP / A2DP Wireless output:Class 2 Max.communication
Unit DimensionsΦ140 x 32mmΦ140 x 32mmPackage Dimensions245x170x50mm245x170x50mmPackage Weight0.5kg0.5kgAccessoriesProtective Travel Case USB cable,English User's ManualProtective Travel Case USB cable, English User's ManualEnvironmentsVindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOperating temperature5°C—40°C5°C—40°CStorage temperature-30°C—55°C-30°C—55°CRechargeable batteryN/A√ Over 4-hours talk time	3.5mm audio port	1 for external speaker	1 for external speaker
Package Dimensions245x170x50mm245x170x50mmPackage Weight0.5kg0.5kgAccessoriesProtective Travel Case USB cable,English User's ManualProtective Travel Case USB cable,English User's ManualEnvironmentsOS requirementsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOperating temperature5°C—40°C5°C—40°CStorage temperature-30°C—55°C-30°C—55°CRechargeable batteryN/A	Package		
Package Weight0.5kg0.5kgAccessoriesProtective Travel Case USB cable,English User's ManualProtective Travel Case USB cable, English User's ManualEnvironmentsVindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOperating temperature5°C—40°C5°C—40°CStorage temperature-30°C—55°C-30°C—55°CRechargeable batteryN/A√ Over 4-hours talk time	Unit Dimensions	Ф140 x 32mm	Ф140 x 32mm
AccessoriesProtective Travel Case USB cable,English User's ManualProtective Travel Case USB cable, English User's ManualEnvironmentsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOperating temperature5°C—40°C5°C—40°CStorage temperature-30°C—55°C-30°C—55°CRechargeable batteryN/AVer 4-hours talk time	Package Dimensions	245x170x50mm	245x170x50mm
AccessoriesUSB cable,English User's ManualUSB cable, English User's ManualEnvironmentsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOperating temperature5°C—40°C5°C—40°CStorage temperature-30°C—55°C-30°C—55°CRechargeable batteryN/A√ Over 4-hours talk time	Package Weight	0.5kg	0.5kg
OS requirementsWindows XP/ Vista/ 7/8/10 Mac OS, AndroidWindows XP/ Vista/ 7/8/10 Mac OS, AndroidOperating temperature5°C—40°C5°C—40°CStorage temperature-30°C—55°C-30°C—55°CRechargeable batteryN/A \checkmark Over 4-hours talk time	Accessories		
OS requirementsMac OS, AndroidMac OS, AndroidOperating temperature5°C—40°C5°C—40°CStorage temperature-30°C—55°C-30°C—55°CRechargeable batteryN/A \checkmark Over 4-hours talk time	Environments		
Storage temperature-30°C—55°C-30°C—55°CRechargeable batteryN/A√ Over 4-hours talk time	OS requirements		
Rechargeable batteryN/A√ Over 4-hours talk time	Operating temperature	5°C—40°C	5°C—40°C
over 4-hours taik unie	Storage temperature	-30°C—55°C	-30℃—55℃
Compliance FCC / CE / RoHS FCC / CE / RoHS/BQB	Rechargeable battery	N/A	Over 4-hours talk time
	Compliance	FCC / CE / RoHS	FCC / CE / RoHS/BQB